

The above curves show the engine's operating characteristics in the range of most normal applications. The engine's maximum speed/power is to be adjusted, should be needed, for the characteristic torque and speed rate.

For selecting a pump engine, the proper gear rate is selected on the diagram by the curve close to the operating point resulting from the engine's oil power and its operating 1:1 ratio. After the ideal line is the engine selected the curve, the recommended maintenance is also indicated on the engine's technical data.

CONTROL TYPE

Castoldi Jet 05: mechanical manual control system.

Castoldi Jet 05: mechanical manual control system.





100

They conducted a survey of attitudes. "In Southern Asia, people are generally very conservative, especially when it comes to gender roles," says Kishor. "In addition, the reproductive health services are often not available, and people are not aware of their rights." In addition, "in many countries, the reproductive health services are not available, and people are not aware of their rights."

*The authors are grateful to the National Natural Science Foundation of China (Grant No. 81273055) and the National Natural Science Foundation of China (Grant No. 81273055) for their financial support.

The publication of the JCR is the critical step. It can be expected completely out of the ordinary experience. The situation, however, remains very different. The publication of the JCR is the critical step. It can be expected completely out of the ordinary experience. The situation, however, remains very different.

Information on the location of the site and the nature of the site is provided in the following table. The table is organized by the type of site and the location of the site. The table is organized by the type of site and the location of the site.

Year	Number of cases
1990	10
1991	15
1992	20
1993	25
1994	30
1995	35
1996	40
1997	45
1998	50
1999	55
2000	60
2001	65
2002	70
2003	75
2004	80
2005	85
2006	90
2007	95
2008	100
2009	105
2010	110
2011	115
2012	120
2013	125
2014	130
2015	135
2016	140
2017	145
2018	150
2019	155
2020	160
2021	165
2022	170
2023	175
2024	180
2025	185
2026	190
2027	195
2028	200
2029	205
2030	210


© 2004 Blackwell Publishing Ltd, *Journal of Internal Medicine* 255: 103–110

© 2004 Blackwell Publishing Ltd *Journal of Internal Medicine* 255: 115–122

Abstract

Tuesday, April 10

[illegible]



The above graph shows the rated operating characteristics for the range of gas turbine engines. The engine (Castoldi Turbodrives 282) can be used to drive loads between 100 and 1500 rpm.

For centrifugal pumps, the rated rpm value is indicated in the drawing for the rated flow to the transfer point (usually 1000 rpm). The engine can be used for the operating point. When the rated rpm is the rated speed, the rated flow is indicated in the drawing for the rated flow (usually 1000 rpm).

CONTROL TYPES

Castoldi Turbodrives 282: electrohydraulic control system.

Castoldi 282: electrohydraulic control system.

Castoldi 282: electrohydraulic control system, operating (control) and manual mode, starting mode and stopping mode.