

55kW (74hp)

Maximum rating (gross intermittent)	55kW (74hp)
At speed	2200rpm
Peak Torque	400 Nm (295 lb-ft)
Peak Torque Speed	1200-1250rpm
Maximum no load governed speed	2200rpm
Nominal idling speed	850-950rpm
Thermodynamic Cycle	Diesel 4 Stroke
Air Intake	TCAE
Arrangement	In-line 4 cyl
Displacement	3.0L
Nominal Bore	92mm (3.62in)
Stroke	112mm (4.41in)



63kW (91hp) to 81kW (108hp)

Turbocharged Aftercooled Electronic 4 cylinder 4.4 litre engines with maximum torque of 516Nm (380 lb-ft)

Maximum rating (gross intermittent)	68kW (91hp)	81kW (108hp)
At speed	2200 rpm	
Peak Torque	433 Nm (319 lb-ft)	516 Nm (380 lb-ft)
Peak Torque Speed	1500 rpm	
Maximum no load governed speed	2450 rpm	
Nominal Idling Speed	850 rpm	
Thermodynamic Cycle	Diesel 4 Stroke	
Air Intake	TCA	
Arrangement	4.4L	
Nominal bore	103 mm (4.06")	
Stroke	132 mm (5.20")	



93kW (125hp) to 108kW (145hp)

Turbocharged Aftercooled Electronic 4 cylinder 4.4 / 4.8 litre engines with maximum torque of 560Nm (413 lb-ft)

Maximum rating (gross intermittent)	93kW (125hp)	108kW (145hp)
At speed	2200 rpm	
Peak Torque	550 Nm (406 lb-ft)	560 Nm (413 lb-ft)
Peak Torque Speed	1500 rpm	
Maximum no load governed speed	2450 rpm	2450 rpm
Nominal Idling Speed	850 rpm	
Thermodynamic Cycle	Diesel 4 Stroke	
Air Intake	TCA	
Arrangement	4.4L	4.8L
Nominal bore	103 mm (4.06")	106 mm (4.17")
Stroke	132 mm (5.20")	135 mm (5.31")



129kW (173hp)

Turbocharged Aftercooled Electronic 4 cylinder 4.8 litre engine with maximum torque of 690Nm (509 lb-ft)

Maximum rating (gross intermittent)	129kW (173hp)
At speed	2050 rpm
Peak Torque	690 Nm (509 lb-ft)
Peak Torque Speed	1500 rpm
Maximum no load governed speed	2125 rpm
Nominal Idling Speed	850 rpm
Thermodynamic Cycle	Diesel 4 Stroke
Air Intake	TCA
Arrangement	4.8L
Nominal bore	106 mm (4.17")
Stroke	135 mm (5.31")

